









PRODUCT NO.	DISCO8SHGET
RoHS compliant	



RECOMMENDED P.C.B. LAYOUT (TOP VIEW)

- NOTES :
- Specification:
    - Operating force: 1000gf Max
    - Operating Temperature: -40° to +85°
    - Storage Temperature: -40° to +85°
    - Mechanical Life: 3000cycles minimum
    - Electrical Life: 2000cycles 25mA 24VDC
  - PLATING:
    - GOLD FLASH 1u"(min.) SOLDER TAIL,
    - 3u" GOLD PLATING ON THE CONTACT AREA,
    - WITH 50u" NICKEL UNDERPLATING OVERALL.

3. PART NUMBER DESCRIPTION



Number	Part Name	Material	Finished
①	Actuator	UL94 V0	White
②	Cover	UL94 V0	Black
③	Movable	Copper Alloy	3u"Gold
④	Terminal	Brass	1u"Gold
⑤	Base	UL94 V0	Black
⑥	Terminal Contact	Brass	3u"Gold

TOLERANCE UNLESS OTHERWISE SPECIFIED	INSPECTION COPY
LINER	PROJECTION
0 ± 0.25	0. ± 2'
.00 ± 0.15	.0 ± 1'
.000 ± 0.10	.00 ± 0.5'

FILE NO.	DISCO8SHGET-A
SIZE	UNIT SCALE SHEET REV.
A4	mm 2 : 1 10F-1 A

**RE** 瑞普特电子股份有限公司  
Dongguan Kingtek Industrial Co., Ltd.

TITLE  
BY DISC SERIES PITCH 2.54mm

PRODUCT FAMILY DISC SERIES  
PRAT NO. DISCO8SHGET

DATE  
2012/04/12